
PRODUCT DATA DRAWING

REVISION HISTORY					
REV	DESCRIPTION	DATE	APPROVED		
-	DCN 50993	08/21			
			SEE PDM		



MATERIAL:

CONNECTORS: SIZE 16 PIN CONTACT (9341-40057) MCX STRAIGHT CRIMP PLUG

RG-179/U CABLE (200-70-118) CABLE:

STRAIN RELIEF: M23053/5

PERFORMANCE:

IMPEDANCE: 75 OHMS FREQ. RANGE: DC TO 3.0 GHz.

NOTES:

SIZE 16 PIN DESIGNED TO MATE TO SIZE 16 SOCKET CONTACT

(9351-40040) ON 7093-0275, OR SIMILAR.
SIZE 16 PIN WILL NOT MATE TO STANDARD SIZE 16 SOCKET CONTACT OR SMPS CONNECTOR.

MATERIAL:	SEE NOTES
FINISH:	SEE NOTES
SURFACE AR	^{EA:} N/A
	PROPRIETARY
IS THE SOLE P ANY REPRODU WITHOUT THE	TION CONTAINED IN THIS DRAW ROPERTY OF SV MICROWAVE, ICTION IN PART OR AS A WHOL WRITTEN PERMISSION OF /E, INC IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES:
	FRACTIONAL: ±1/64 ANGULAR: X° ±1°0 X°X' +15'
	DECIMAL: .X ±.030 .XX +.010
1	VVV - 00F

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994

THIRD ANGLE PROJECTION		

UNLESS OTHERWISE SPECIFIED

1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS]
2) ALL DIMENSIONS ARE AFTER PLATING.
3) BREAK CORNERS & EDGES .005 R. MAX.
4) CHAM. 15T & LAST THREADS.
5) SURFACE ROUGHNESS 63-MIL-STD-10.
6) DIA'S ON COMMON CENTERS TO BE CONCENTRIC
WITHIN .005 T.I.R.
7) PERMOVE ALL BILIPERS.

APPROVED:

7) REMOVE ALL BURRS	
DRAWN:	TSW 08/26/2
CHECKED:	SEE PDM

SEE PDM

MICROWAVE SIZE 16 STR. PIN TO MCX STD DILIC DC170 CARLE

	SIR. PLUG RG1/9 CABLE		
/21			ASSEMBLY
	SIZE	DWG. NO.	
Λ	D	2110. 110.	7093-0276

1093-0216 В SHEET 1 OF 1 SCALE: 4:1