
PRODUCT DATA DRAWING

REVISION HISTORY DATE APPROVED DESCRIPTION DCN 48417 6/24 SEE PDM



MATERIAL:

CONNECTORS:

FLEXIBLE .047 CABLE (200-70-479) CABLE:

SHRINK TUBING: M23053/5

PERFORMANCE:

IMPEDANCE: 50 OHMS FREQ. RANGE: DC TO 40.0 GHz.

SMPM VITA 67.3 BACKPLANE CONTACT (3221-40071) SIZE 12 SMPM 38999 SOCKET CONTACT (SF3211-60153)

MATERIAL: SEE NOTES FINISH: SEE NOTES SURFACE AREA: N/A **PROPRIETARY**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' ±15' .X ±.030 .XX ±.010 .XXX ±.005

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994

DRAWN: THIRD ANGLE PROJECTION CHECKED: APPROVED:

UNLESS OTHERWISE SPECIFIED

JPM 6/28/24

SEE PDM

SEE PDM

1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS]
2) ALL DIMENSIONS ARE AFTER PLATING,
3) BREAK CORNERS & EDGES 005 R. MAX.
4) CHAM. 1ST & LAST THREADS.
5) SURFACE ROUGHNESS 63-MIL-STD-10.
6) DIA: S ON COMMON CENTERS TO BE CONCENTRIC WITHIN. 005 T.I.R.
7) REMOVE ALL BURRS

TABLE 1 SV P/N OAL 12.000 [304.80] 7032-10044 7032-10043 6.000 [152.40]

> MICROWAVE SMPM STR. F TO SIZE 12

STR. SOCKET STANDARD FLEXTRA CABLE ASSEMBLY

7032-10043-10044 В SCALE: 4:1