


PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	NRN 44387	11/19	SEE PDM
A	DCN 51649	05/22	



MATERIAL:

CONNECTORS: BMA (SIZE 8) D38999 SOCKET CONTACT (SF9411-6000)
SMA PLUG (SF2906-6002)

CABLE: T-FLEX 405

SHRINK TUBING: M23053/5



PERFORMANCE:

IMPEDANCE: 50 OHMS

FREQ. RANGE: DC TO 18.0 GHz

NOTE:
1. ALL SOCKET CONTACTS DESIGNED FOR SERIES I, III OR IV.

SV P/N	OAL
7093-0178	12.000
7093-0179	24.000

MATERIAL: SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: $\pm 1/64$ ANGULAR: X° $\pm 1^{\circ}0'$ X°X' $\pm 15'$	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63-MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS	 www.svmicrowave.com	
FINISH: SEE NOTES	DECIMAL: .X $\pm .030$.XX $\pm .010$.XXX $\pm .005$	INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994	TITLE: BMA (SIZE 8) D38999 SOCKET CONTACT TO SMA MALE FOR Ø.085 T-FLEX 405 CABLE ASSEMBLY	
SURFACE AREA: N/A	THIRD ANGLE PROJECTION 	DRAWN: SJ 11/08/19	SIZE DWG. NO. B 7093-0178-0179	
PROPRIETARY THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.		CHECKED: SEE PDM	APPROVED: SEE PDM	SCALE: 3:1
				SHEET 1 OF 1